




## Puller

The CM Puller is designed for heavy-duty construction and industrial applications. Used to pull, lift, drag or stretch, it features:


- Tough aluminum alloy construction and powder coat finish
- Weatherproof for outdoor service
- Simple construction with fewer parts for ease of maintenance and lower inventories
- Hoistaloy hardened steel link type load chain for strength, long wear life and flexibility
- Weatherized Weston-type automatic braking system for positive load control
- Easy, one-hand operation and control — only 58 pounds of pull required for  $\frac{3}{4}$  ton model capacity
- Forged upper and lower hooks with latches standard
- Free wheeling for fast and easy attachment to load
- Upper and lower Latchlok hooks available for all capacities
- Optional Load Limiter protection device stops transmission of lever forces protecting against dangerous overload
- Optional anchor sling simplifies attachment to allow anchor hook to swivel in tight space applications ( $\frac{3}{4}$  &  $1\frac{1}{2}$  ton units only)
- Optional Load Sentry warns of overload condition
- Optional zinc-plated chain available
- Unlimited lift
- Lifetime warranty
- Metric rated
- Made in U.S.A.



**Optional Load Limiter**



**Optional anchor sling ( $\frac{3}{4}$  and  $1\frac{1}{2}$  ton)**



**Latchlok type hook**



**$\frac{3}{4}$  ton**

### Puller specifications - standard unit

| Rated capacity* (tons) | Product code | Standard lift† (ft.) | Pull to lift full loads (lbs.) | Minimum distance between hooks (in.) | Lever length (in.) | Reeving | Hook throat openings (in.) | Approx. shipping weight (lbs.) |
|------------------------|--------------|----------------------|--------------------------------|--------------------------------------|--------------------|---------|----------------------------|--------------------------------|
| $\frac{3}{4}$          | 4043         | 5                    | 58                             | $10\frac{3}{4}$                      | $21\frac{1}{4}$    | 1       | $1\frac{1}{32}$            | 16                             |
| $1\frac{1}{2}$         | 4045         | 5                    | 89                             | $14\frac{1}{4}$                      | $21\frac{1}{4}$    | 1       | $1\frac{1}{8}$             | 26                             |
| 3                      | 4047         | 5                    | 95                             | $16\frac{15}{16}$                    | $21\frac{1}{4}$    | 2       | $1\frac{7}{32}$            | 38                             |
| 6                      | 4050         | 5                    | 96                             | $21\frac{3}{8}$                      | $21\frac{1}{4}$    | 4       | $1\frac{3}{4}$             | 73                             |

† Can be supplied with lifts longer than 5 feet

### Optional kits

| Rated capacity* (tons) | Load Limiter |                                | Load Sentry kit |                    |                                | Anchor sling kit |                                |
|------------------------|--------------|--------------------------------|-----------------|--------------------|--------------------------------|------------------|--------------------------------|
|                        | Product code | Approx. shipping weight (lbs.) | Product code    | Lever length (in.) | Approx. shipping weight (lbs.) | Product code     | Approx. shipping weight (lbs.) |
| $\frac{3}{4}$          | 4190         | $8\frac{1}{4}$                 | 4096            | $23\frac{3}{4}$    | $4\frac{1}{2}$                 | 4071             | 2                              |
| $1\frac{1}{2}$         | 4191         | $8\frac{1}{4}$                 | 4098            | $23\frac{3}{4}$    | $4\frac{1}{2}$                 | 4072             | $4\frac{3}{4}$                 |
| 3                      | 4191         | $8\frac{1}{4}$                 | 4098            | $23\frac{3}{4}$    | $4\frac{1}{2}$                 | —                | —                              |
| 6                      | 4191         | $8\frac{1}{4}$                 | 4098            | $23\frac{3}{4}$    | $4\frac{1}{2}$                 | —                | —                              |